

HDMI VGA signal decentralized wall extender

Model:HV

Features

- Disperse and extend the 4K HDMI VGA+3.5mm audio to the remote receiver display through the network cable.
- Resolution 1080P 60Hz up to 100 meters, resolution 4K 60Hz (4:2:0) up to 70 meters.
- The wall panel is beautifully designed to hide all connecting wires behind the panel.
- Support POC unilateral power supply function.
- Support HDMI2.0 (4:2:0), HDCP2.2, HDR.
- The picture quality is clear and there is no problem of mosaic compression.
- The receiver HD2700K can play and display at a distance.
- Can be directly connected to GMS series matrix switchers.

Specification

MODEL NAME	HV
Input	1 x HDMI/ 1 x VGA+3.5mm
Output	1 x RJ-45 port (HDBaseT)
Support resolution	1080P 60Hz up to 100 meters, 4K 60Hz (4:2:0) up to 70 meters.
Protocol standard	Support HDMI2.0, HDCP2.2
Connection cable length	Input and output can be connected to a maximum of 5 meters HDMI cable
Power supply	DC 12V 1.5A (POC)
Weight	0.5kg
Dimensions	114*72*32.7 mm

Diagram



Package contents

- 1 X HV
- 1 X 12V 1.5A Adapter
- 1 X User Manual